

# RUBBERWORX

## BLUE PVC DISCHARGE

This light-duty PVC water discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. PVC tube and cover are designed to handle residual chemicals in water transfer applications.



- TUBE:** PVC
- REINFORCEMENT:** TEXTILE BRAID
- COVER:** BLUE PVC
- TEMPERATURE:** -5°F to 170°F
- BRANDING:** PVC DISCHARGE 80 PSI
- PACKAGING SPECIFICATIONS:** 100' AND 50' PRE COUPLED SECTIONS

SA #	ID (IN)	LENGTH	COUPLINGS	COUPLINGS MATERIAL	WP (PSI)	BURST (PSI)	WEIGHT ASSEMBLY	PACKAGING
1009-200-0600-ALCXE	2.00	50	MXFCAM	ALUMINUM	80	240	5.60	50'
1009-200-1200-ALCXE	2.00	100	MXFCAM	ALUMINUM	80	240	11.20	100'
1009-300-0600-ALCXE	3.00	50	MXFCAM	ALUMINUM	80	240	9.60	50'
1009-300-1200-ALCXE	3.00	100	MXFCAM	ALUMINUM	80	240	19.20	100'
1009-400-0600-ALCXE	4.00	50	MXFCAM	ALUMINUM	70	210	13.40	50'
1009-400-1200-ALCXE	4.00	100	MXFCAM	ALUMINUM	70	210	26.80	100'
1009-600-0600-ALCXE	6.00	50	MXFCAM	ALUMINUM	60	180	23.50	50'
1009-600-1200-ALCXE	6.00	100	MXFCAM	ALUMINUM	60	180	47.00	100'