


RUBBERWORX

FDA CLEAR PVC TUBING

RUBBERWORX™ 0.25" x 0.38" FDA PVC TUBING 

A lightweight PVC tubing for use in liquid drain or transportation, meets FDA requirements. For use as a lightweight gasket or grommet material. 70A Durometer tubing for a wide variety of applications.

TUBE:	FDA COMPLIANT PVC
COVER:	FDA COMPLIANT PVC
TEMPERATURE:	25°F to 150°F
BRANDING:	0.25" x 0.38" FDA PVC TUBING 55 PSI
PACKAGING SPECIFICATIONS:	100', 300'
DUOMETER:	70A

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT (LB/FT)	PACKAGING
1015-013-025	0.125	0.25	65	195	NA	NA	0.02	100', 300'
1015-019-025	0.188	0.25	50	150	NA	NA	0.012	100', 300'
1015-019-031	0.188	0.31	55	165	NA	NA	0.027	100', 300'
1015-019-038	0.188	0.38	60	180	NA	NA	0.045	100', 300'
1015-025-038	0.25	0.38	55	165	NA	NA	0.034	100', 300'
1015-025-044	0.25	0.44	58	174	NA	NA	0.055	100', 300'
1015-025-050	0.25	0.50	60	180	NA	NA	0.08	100', 300'
1015-031-044	0.31	0.44	55	165	NA	NA	0.04	100', 300'
1015-031-050	0.31	0.50	58	174	NA	NA	0.065	100', 300'
1015-031-056	0.31	0.56	60	180	NA	NA	0.094	100', 300'
1015-038-050	0.38	0.50	50	150	NA	NA	0.047	100', 300'
1015-038-056	0.38	0.56	55	165	NA	NA	0.075	100', 300'
1015-038-063	0.38	0.63	60	180	NA	NA	0.107	100', 300'
1015-050-063	0.50	0.63	50	150	NA	NA	0.06	100', 300'
1015-050-069	0.50	0.69	55	165	NA	NA	0.095	100', 300'
1015-050-075	0.50	0.75	60	180	NA	NA	0.134	100', 300'
1015-063-075	0.63	0.75	45	135	NA	NA	0.082	100', 300'
1015-063-081	0.63	0.81	50	150	NA	NA	0.116	100', 300'

RUBBERWORX

FDA CLEAR PVC TUBING

RUBBERWORX™ 0.25" x 0.38" FDA PVC TUBING



A lightweight PVC tubing for use in liquid drain or transportation, meets FDA requirements. For use as a lightweight gasket or grommet material.

TUBE:	FDA COMPLIANT PVC
COVER:	FDA COMPLIANT PVC
TEMPERATURE:	25°F to 150°F
BRANDING:	0.25" x 0.38" FDA PVC TUBING 55 PSI
PACKAGING SPECIFICATIONS:	100', 300'
DUOMETER:	70A

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT (LB/FT)	PACKAGING
1015-063-088	0.63	0.88	55	165	NA	NA	0.161	100', 300'
1015-075-100	0.75	1.00	35	105	NA	NA	0.188	100', 300'
1015-075-113	0.75	1.13	30	90	NA	NA	0.30	100', 300'
1015-075-125	0.75	1.25	40	120	NA	NA	0.429	100', 300'
1015-088-113	0.88	1.13	45	135	NA	NA	0.214	100', 300'
1015-088-125	0.88	1.25	25	75	NA	NA	0.341	100', 300'
1015-100-125	1.00	1.25	35	105	NA	NA	0.241	100', 300'
1015-100-138	1.00	1.38	40	120	NA	NA	0.382	100', 300'
1015-100-150	1.00	1.50	35	105	NA	NA	0.536	100', 300'
1015-125-150	1.25	1.50	40	120	NA	NA	0.148	100'
1015-125-163	1.25	1.63	45	135	NA	NA	0.231	100'
1015-125-175	1.25	1.75	30	90	NA	NA	0.322	100'
1015-150-188	1.50	1.88	35	105	NA	NA	0.271	100'
1015-150-200	1.50	2.00	25	75	NA	NA	0.375	100'
1015-200-250	2.00	2.50	30	90	NA	NA	0.482	100'