

RUBBERWORX

HD WATER DISCHARGE 200-150 PSI



This extra heavy-duty water discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. Abrasion and ozone resistant EPDM/SBR blend cover for heavy duty industrial applications. NR/SBR tube designed to handle residual chemicals in water transfer applications.

TUBE:	BLACK NR/SBR BLEND
REINFORCEMENT:	4 PLY TEXTILE
COVER:	BLACK EPDM/SBR BLEND
TEMPERATURE:	-25°F to 180°F
BRANDING:	WATER DISCHARGE 200 PSI
PACKAGING SPECIFICATIONS:	100' COILS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
1023103-150	1.50	2.01	200	600	NA	NA	0.99	100'
1023103-200	2.00	2.52	200	600	NA	NA	1.29	100'
1023103-250	2.50	3.09	200	600	NA	NA	1.55	100'
1023103-300	3.00	3.59	200	600	NA	NA	2.17	100'
1023103-400	4.00	4.61	150	450	NA	NA	2.72	100'
1023103-600	6.00	6.73	150	450	NA	NA	5.75	100'
1023103-800	8.00	8.78	150	450	NA	NA	8.51	100'
1023103-1000	10.00	10.95	150	450	NA	NA	10.83	100'
1023103-1200	12.00	12.90	150	450	NA	NA	12.44	100'