

RUBBERWORX

AIRMAX-E DUCTING

This sewn ducting is designed for air in temporary ducting systems. For use with air movement, air conditioning and dehumidification. PVC polyester has excellent UV resistance. Large pitch allows for significant compression and flexibility. Meets flame resistant UL94VTM-O, California Fire Marshal, and NFPA701 specifications



- TUBE:** PVC POLYESTER
- REINFORCEMENT:** CARBON STEEL HELIX
- COVER:** YELLOW & BLACK PVC POLYESTER
- TEMPERATURE:** -20°F to 180°F
- BRANDING:** SEWN DUCTING
- PACKAGING SPECIFICATIONS:** 25' SECTIONS
- OPTIONS:** SEWN HEAVY DUTY WEAR STRIP
- OPTIONS:** WIRE ROPE COUPLING

SA #	ID (IN)	PITCH(IN)	WEIGHT OZ/YD ²	PACKAGING
D005224-600	6	6	13.00	25'
D005224-800	8	6	13.00	25'
D005224-1000	10	6	13.00	25'
D005224-1200	12	6	13.00	25'
D005224-1400	14	6	13.00	25'
D005224-1600	16	6	13.00	25'
D005224-1800	18	6	13.00	25'
D005224-2000	20	6	13.00	25'
D005224-2400	24	6	13.00	25'